

LED Panel IP65

- LED panel IP65 (LED panel and power supply with IP65 protection class)
- Ideal for swimming pools, food production, canteen kitchens, outdoor areas
- High colour rendering value of CRI>90
- Flicker-free / Flicker-free power supply unit
- Uses high-quality SAMSUNG® LEDs
- 5-year manufacturer's warranty / service life 50,000 hours (manufacturer's information)

product image



	LED panel IP65 120x30cm	LED panel IP65 62x62cm	LED panel IP65 60x60cm
Part Number	ILCLP195K4CW	ICLP620K4CW	ILCLP595K4CW
Besonderheiten	<ul style="list-style-type: none"> • Flicker free power supply unit • Surface resistant to chlorine 	<ul style="list-style-type: none"> • Flicker free power supply unit • Surface resistant to chlorine 	<ul style="list-style-type: none"> • Flicker free power supply unit • surface resistant to chlorine
Housing colour	white		
Power	40 Watt		
Light colour	4000K (840) neutral white		
Luminous flux	3600 Lumen		
Beam angle	120° degrees		
Colour rendering Ra /CRI	CRI92		
dimnable	Yes 1-10V	Yes 1-10V	Yes 1-10V

www.cologne-led.de

Lösungen für gewerbliche Energieeffizienz

Adresse: Neusser Strasse 422c / 50733 Köln

Kontakt: Hr. Oliver Rothweiler

Tel.: +49-177-6027983

Fax: 0221-9924574

E-Mail: team@cologne-led.de

Fest.: 0221- 29821660

LED Panel IP65

Specified service life	50,000 hours	50,000 hours	50,000 hours
Manufacturer's warranty	5 years	5 years	5 years
Power factor Cos-phi:	Cos-phi: 0,9	Cos-phi: 0,9	Cos-phi: 0,9
Energy efficiency class	A⁺	A⁺	A⁺
dimensions	Length: 1195mm width: 295mm height: 15mm	L: 620mm W: 620mm H: 15mm	L: 595mm W: 595mm H: 15mm
power usage 1000 hour	40 kWh	40 kWh	40 kWh
Schutzart	IP65	IP65	IP65
Protection class	aluminium / PMMA	aluminium / PMMA	aluminium / PMMA
Power supply	220-250V 50/60Hz	220-250V 50/60Hz	220-250V 50/60Hz
Operating temperature	-10~45°C	-10~45°C	-10~45°C
manufacturer	Interlight	Interlight	Interlight